

UMAY LWS-2 CONTROL UNIT



UMAY LWS-2 CONTROL UNIT



- **UMAY LWS-2 Control Unit** which can control Laser Warning system and smoke grenade system, can switch between laser and smoke grenade system menus easily thanks to its touch screen.
- Laser warning system transmits:
 - Sensor status
 - Angle of detected laser
 - Class
 - Band options to the user.
- Control unit with digital screen, provides easy use for the user by displaying on-vehicle schematic on the screen.

GENERAL SPECIFICATIONS

» Laser warning system control capability	» Power Consumption: 24 VDC nominal (16-32 V)
» Opportunity to control laser warning system and smoke grenade automatically and switch between systems	» Dimensions: 180x155x116 ±5 mm
» Capability to control up to 16 smoke grenades	» Weight: Control Unit: 1.9 ±0.3 kg
» Built-In Test Function (BIT)	» IP67 Water and Dust Ingress Protection
» Capability to detect and control two different types of smoke grenades	» Production as per IPC-A-610G Class 3 Standards PC
» Communication Interface: CAN-BUS	» Storage Temperature: -55°C / +85°C
» Operating Temperature: -32°C / +49°C	» Capability to Communicate with Other Systems

BUTTON SPECIFICATIONS



1. MAIN SCREEN	5. The Test button is reserve right now.
2. The alarm could clear by using Fn + Alarm reset buttons.	6. BIT Button
3. You will change mode from Battle to Peace.	7. Activates function.
4. You will go into the Button Config.	8. Info button.

UMAY LW 2000 ARMORED VEHICLE APPLICATION

FULL PROTECTION
360°

