





UMAY DC-10 CONTROL UNIT

- UMAY DC-10 Manufactured and tested in accordance with NATO Standards. It can fire up to 15 barrels simultaneously, separately or together in certain configurations.
- It is protected against counter attacks thanks to its Advanced Control box, it is easy to use with its user-friendly interface, and past operations can be examined with its record keeping feature. It can also communicate directly with the vehicle with the CANBUS infrastructure.



GENERAL SPECIFICATIONS			
» Capability to control up to 15 smoke grenades	» Dimensions: 187x112x48 ±5 mm		
» Built-In Test Function (BIT)	» Weight: Control Unit: 0.42 ±0.3 kg		
» Capability to control different types of smoke grenades	» IP67 Water and Dust Ingress Protection		
» Communication Interface: CAN-BUS	» Production as per IPC-A-610G Class 3 Standards PC		
» Operating Temperature: -32°C / +49°C	» Storage Temperature: -55°C / +85°C		
» Power Consumption: 24 VDC nominal (16-32 V)	» Capability to Communicate with Other Sys- tems		

BUTTON SPECIFICATIONS



1.	RETURN FUNCTION BUTTON	5.	JOYSTICK FOR ADJUSTING
2.	NIGHT VISION/ DAY TIME BUTTON	6.	POWER ON/OFF
3.	SELECT FIRING OPTIONS	7.	BIT/BUILT-IN-TEST BUTTON
4.	FIRE	8.	INFO