

**"The Best Defense
is a good Offense"**

**15 BARRELS
GRENADE LAUNCHER**



COLOR



RAL 1000



RAL 6003



RAL 5002



RAL 9010



RAL 9005

LA-ML15 GRENADE LAUNCHER

Grenade Launcher for Suppression and Riot Control

•**Type:** Fully Automatic Grenade Launcher designed for suppression and riot control missions.

•**Targeting System:** Features optional color night vision and infrared (IR) movement detection to monitor and engage in low-visibility conditions.

•**Non-Lethal Ammunition:** Compatible with a range of non-lethal ammunition options, including standard tear gas, rubber bullets, and flashbangs, to safely disperse crowds and neutralize threats.

•**Precision Targeting:** Advanced targeting system allows for accurate delivery of non-lethal munitions, minimizing the risk to civilians and ensuring mission success.

•**Automatic Fire Control:** Automated firing capabilities facilitate rapid response in dynamic crowd control situations.

Smoke Launcher System for Mission Support

•**Operational Role:** Provides tactical support for missions involving crowd management and riot control.

•**Defensive Maneuver:** Deploys smoke cartridges to create a visual barrier, enabling strategic retreats or advances without escalation.

•**Cover for Forces:** Offers concealment for maneuvering support forces into position during peacekeeping operations.

•**Battery :** 2 Hours Operational Battery and 60 times firing.

•**Protection After Engagement:** Used after non-lethal engagements to prevent targeting of security forces during repositioning.

•**Asset Safety:** Ensures the safety of valuable tactical vehicles during operations involving large gatherings.

•**Command Vehicle Utility:** Supports command post vehicles in maintaining operational control and safety during public order events.


Specification		Value	Unit
Operating Voltage		10.5-14 18-32	VDC
Firing Range	Short (Low Velocity)	20-150 meters	
	Long (High Velocity)*	150-800 meters	
Ammunition Capacity		15	Pieces
Shooting Option		Single Fire	Pieces
		Triple Fire	
		Quintuple Fire	
		All Fire	
Operating Temperature		-32 / +55	°C
Body		Aluminum Anodized Body- 10 years corrosion warranty	
Firing Pin / System Warranty		10.000 Times shooting / 2 Years	
System Components		Remote Controller, Launcher, Harness	
Length		155 ±5	Milimeters
Height		380±5	Milimeters
Width		722±5	Milimeters
Barrel Length		200±5	Milimeters
Overall Weight(Max.)		38±2	Kilograms
Camera		Full Hd Color Infrared Camera	
MIL-SPEC Standards		EMI/EMC : MIL-STD-461G	
		EMI/EMC : MIL-STD-1275E	
		Environmental : MIL-STD-810H	

*High Velocity rifled barrels are optional and weight and length of the unit is changing. Please contact with us to have more information



LA-ML15

Grenade Launcher with optional colored night vision




Range is : ±45°

Horizontal Angle

0-120° Vertical

Angle 10 meters to

150 meters range



CONN2 D38999/26WD19PA	
A	BAT+
B	BAT+
C	BAT+
D	BATGR
E	BATGR
F	BATGR
G	TRIG_BAT
H	SWITCH_BOOST
J	+12V_CU
K	CAM+12V (RED)
L	CAM SIGNAL (YELLOW/WHITE)
M	CAM GND (BLACK)
N	CANH
P	CANL
SHIELD	

MILITARY STANDARDS

MIL-STD 810

MIL-STD 461

MIL-STD 1275